

# Specifications

		ST4301K	ST5501K	ST6501K
<b>Panel</b>	Screen Size (inch)	43"	55"	65"
	Backlight/Lightsource	D-LED	D-LED	D-LED
	Active Area (horizontal × vertical)(mm)	941.184(H)mm × 529.416(V)mm	1209.6(H)mm × 680.4(V)mm	1432.5(H)mm × 807.5(V)mm
	Resolution (pixels)	UHD 3840 × 2160	UHD 3840 × 2160	UHD 3840 × 2160
	Brightness (typical)	350 nits	350 nits	450 nits
	Contrast Ratio (typical)	1200:1	1200:1	1200:1
	Viewing Angle (horizontal/vertical)	178° / 178°	178° / 178°	178° / 178°
	Aspect Ratio	16:9	16:9	16:9
	Light Life (typical)	30,000hrs	30,000hrs	30,000hrs
	Display Orientation	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait
<b>Audio</b>	Internal Speaker (Amp)	5W × 2	5W × 2	5W × 2
	Audio Line In/Out (3.5mm)	No / x1	No / x1	No / x1
<b>Connectivity</b>	VGA In/Out	x1 / No	x1 / No	x1 / No
	DVI In/Out	x1 / No	x1 / No	x1 / No
	HDMI In/Out	x2 / No	x2 / No	x2 / No
	Display Port In/Out	x1 / No	x1 / No	x1 / No
	USB port (Type A)	x3 (2.0)	x3 (2.0)	x3 (2.0)
	RJ45 Port In/Out	x1 / No	x1 / No	x1 / No
<b>Power</b>	AC/DC In	AC	AC	AC
	AC Power Switch	Yes	Yes	Yes
	Voltage	100V ~ 240V, 50Hz / 60Hz	100V ~ 240V, 50Hz / 60Hz	100V ~ 240V, 50Hz / 60Hz
	Power Consumption (typical/standby )	65W≤0.5W	TBD	TBD
<b>Mechanical</b>	Dimension (WxHxD) (mm)	969.9 × 558.3 × 84.8(mm)	1243.2x714x69.6(mm)	1487.5x862.5x94.7 (mm)
	Bezel Width (top/bottom/left/right) (mm)	13.9/13.9/13.9/13.9 mm	13.9/13.9/13.9/13.9 mm	28.7/28.7/28.7/28.7 mm
	Weight (w/o Packing/ w/ Packing) (kg)	10.4kg / 12.9kg	10.4kg / 12.9kg	TBD
	Wall Mounting (VESA) (mm)	200x400 (4-M6)	400x400 (4-M6)	200x400 (4-M6)
<b>Environment</b>	Operation Temperature	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C
	Storage Temperature	-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C
	Usage (Hour/Day)	18 / 7	18 / 7	18 / 7
<b>OSD</b>	On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese (24L)	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese (24L)	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese (24L)
<b>Software</b>	Multiple Display Control (MDA) Support	Yes	Yes	Yes
	X-Sign (please check X-Sign website for detailed compatibility info.)	Yes	Yes	Yes
<b>Accessory</b>	Remote Control	Yes	Yes	Yes
	Power Cord (by region)	Yes	Yes	Yes
	VGA Cable	Yes	Yes	Yes
	HDMI Cable	Yes	Yes	Yes
	Quick Start Guide	Yes	Yes	Yes
	User's Manual Electronic File	Yes	Yes	Yes
	RS232 Cable	Yes	Yes	Yes